SAFETY DATA SHEET

1. Identification

in identification		
Product identifier	INO SOLUTIONS INO-AES100 GLASS CLEANER	
Other means of identification		
Product code	1000005788	
Recommended use	cleaner	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name	DISSAN MAINTENANCE PRO	
Address	9280, BOULEVARD DU GOLF	
	VILLE D 'ANJOU, QC H1J 3A' Canada	1
Telephone	General Assistance	514-789-6363
E-mail	Not available.	
Emergency phone number	Emergency - US	1-866-836-8855
	Emergency - Outside US	1-952-852-4646
Supplier	Not available.	
2. Hazard(s) identification		
z. nazaru(5) identification		
Physical hazards	Gases under pressure	Liquefied gas
.,	Gases under pressure Not classified.	Liquefied gas
Physical hazards		Liquefied gas
Physical hazards Health hazards		Liquefied gas
Physical hazards Health hazards		Liquefied gas
Physical hazards Health hazards		Liquefied gas
Physical hazards Health hazards Label elements	Not classified.	Liquefied gas
Physical hazards Health hazards Label elements Signal word	Not classified.	
Physical hazards Health hazards Label elements Signal word Hazard statement	Not classified.	
Physical hazards Health hazards Label elements Signal word Hazard statement Precautionary statement	Not classified.	may explode if heated.
Physical hazards Health hazards Label elements Signal word Hazard statement Precautionary statement Prevention	Not classified. Warning Contains gas under pressure; Observe good industrial hygier	may explode if heated.
Physical hazards Health hazards Label elements Signal word Hazard statement Precautionary statement Prevention Response	Not classified. Warning Contains gas under pressure; Observe good industrial hygier Wash hands after handling.	may explode if heated. ne practices.
Physical hazards Health hazards Label elements Signal word Hazard statement Precautionary statement Prevention Response Storage	Not classified. Warning Contains gas under pressure; Observe good industrial hygien Wash hands after handling. Protect from sunlight. Store in	may explode if heated. ne practices. a well-ventilated place.
Physical hazards Health hazards Label elements Signal word Hazard statement Precautionary statement Prevention Response Storage Disposal	Not classified. Warning Contains gas under pressure; Observe good industrial hygien Wash hands after handling. Protect from sunlight. Store in Dispose of waste and residues	may explode if heated. ne practices.
Physical hazards Health hazards Label elements Signal word Hazard statement Precautionary statement Prevention Response Storage	Not classified. Warning Contains gas under pressure; Observe good industrial hygien Wash hands after handling. Protect from sunlight. Store in	may explode if heated. ne practices. a well-ventilated place.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethyl Alcohol		64-17-5	3.343
2-Butoxyethanol		111-76-2	2.895
Propane		74-98-6	1.771
Butane		106-97-8	1.729
Other components below re	portable levels		90.26302

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (I).

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No specific first aid measures noted.
Ingestion	Not likely, due to the form of the product.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Keep away from heat/sparks/open flames/hot surfaces No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll,

slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values Components	Туре	Value
2-Butoxyethanol (CAS	TWA	20 ppm
111-76-2)		20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (Occupation	al Health & Safety Code, Sc	hedule 1, Table 2)
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	97 mg/m3
		20 ppm
Butane (CAS 106-97-8)	TWA	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Canada. British Columbia OELs. (C	Occupational Exposure Limit	ts for Chemical Substances, Occupational Health and
Safety Regulation 296/97, as amen		
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	750 ppm
	TWA	600 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Canada. Manitoba OELs (Reg. 217/	2006, The Workplace Safety	And Health Act)
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Canada. Ontario OELs. (Control of	Exposure to Biological or C	hemical Agents)
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	TWA	800 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Canada. Quebec OELs. (Ministry o Components	f Labor - Regulation Respect Type	ting the Quality of the Work Environment) Value
2-Butoxyethanol (CAS 111-76-2)	TWA	97 mg/m3
···· ···		20 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Ethyl Alcohol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

ACGIH Biological Expos	ure Indices			
Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
* - For sampling details, pl	ease see the source	document.		
Appropriate engineering controls	should be matc or other engine	hed to conditions. If ap ering controls to mainta	olicable, use proc in airborne levels	our) should be used. Ventilation rates cess enclosures, local exhaust ventilation s below recommended exposure limits. If borne levels to an acceptable level.
ndividual protection measu	es, such as person	al protective equipme	nt	
Eye/face protection	Wear safety gla	sses with side shields	(or goggles).	
Skin protection				
Hand protection	Wear appropria supplier.	te chemical resistant g	oves. Suitable gl	oves can be recommended by the glove
Other	Wear suitable p	rotective clothing.		
Respiratory protection	-	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.		
Thermal hazards	Wear appropria	te thermal protective cl	othing, when nec	essary.
General hygiene considerations	after handling th		eating, drinking, a	nal hygiene measures, such as washing and/or smoking. Routinely wash work nnts.

9. Physical and chemical properties

, ,	•
Appearance	
Physical state	Gas.
Form	Aerosol. Liquefied gas.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	9.1 - 10.1 estimated
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	80 - 100 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Product name: INO SOLUTIONS S 1	

Viscosity Not available. Other information Aerosol spray enclosed space **Deflagration density** > 2.52 g/cm3 Tested Aerosol spray ignition < 15 cm Tested estimated distance **Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing. 0.977 - 0.997 Specific gravity VOC (Weight %) 9.5 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2-Butoxyethanol (CAS 11	1-76-2)	
Acute		
Dermal		
LD50	Guinea pig	7.3 ml/kg, 4 Days
		0.23 ml/kg, 24 Hours
	Rabbit	435 mg/kg, 24 Hours
		0.68 ml/kg, 24 Hours
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1414 mg/kg
	Mouse	1519 mg/kg

Components	Species	Test Results	
	Rat	1746 mg/kg	
Butane (CAS 106-97-8)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
Ethyl Alcohol (CAS 64-17-5)			
<u>Acute</u>			
Inhalation	0.1		
LC50	Cat	85.41 mg/l, 4.5 Hours	
		43.68 mg/l, 6 Hours	
	Mouse	> 60000 ppm	
		79.43 mg/l, 134 Minutes	
	Rat	> 115.9 mg/l, 4 Hours	
		51.3 mg/l, 6 Hours	
Oral			
LD50	Monkey	6000 mg/kg	
	Mouse	10500 ml/kg	
	Pig	> 5000 mg/kg	
	Rat	10470 mg/kg	
		7800 ml/kg	
Propane (CAS 74-98-6)		-	
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
	be based on additional componer		
Skin corrosion/irritation	Prolonged skin contact may ca		
Serious eye damage/eye	Direct contact with eyes may o	cause temporary initiation.	
Respiratory or skin sensitizatio	n		
Canada - Alberta OELs: Irri			
2-Butoxyethanol (CAS 1		Irritant	
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to	o cause skin sensitization.	
Germ cell mutagenicity			
0 7			
Carcinogenicity			
ACGIH Carcinogens			
2-Butoxyethanol (CAS 1	11-76-2)	A3 Confirmed animal carcinogen with unknown relevance to	
Canada - Manitoba OELs: c	arcinogenicity	humans.	
2-BUTOXYETHANOL (E		Confirmed animal carcinogen with unknown relevance to humans	
ETHANOL (CAS 64-17-	5)	Confirmed animal carcinogen with unknown relevance to humans.	
IARC Monographs. Overall	Evaluation of Carcinogenicity		
2-Butoxyethanol (CAS 1		3 Not classifiable as to carcinogenicity to humans.	

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	May be harmful if absorbed through skin.	
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.	

12. Ecological information

			as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environmen	
Product		Species	Test Results	
INO SOLUTIONS S-10	00 GLASS CLEAN	ER		
Aquatic				
Crustacea	EC50	Daphnia	13838.1602 mg/l, 48 hours estimated	
Components		Species	Test Results	
2-Butoxyethanol (CAS	111-76-2)			
Aquatic				
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours	
Ethyl Alcohol (CAS 64	-17-5)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas	s) > 100.1 ma/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient	n-octanol / water (log Kow)	
2-Butoxyethanol	0.83	
Butane	2.89	
Ethyl Alcohol	-0.31	
Propane	2.36	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

UN number

TDG

UN proper shipping name Transport hazard class(es)	AEROSOLS, non-flammable
Class	2.2
Subsidiary risk	-
Packing group	- If <1L: Limited Quantity
Environmental hazards	D
	Read safety instructions, SDS and emergency procedures before handling.
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
· · ·	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.





General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable. Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date	11-11-2015
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names